

IN-SITU MONITORING OF DRILLING MUD VISCOSITY USING ADVANCED SENSOR TECHNOLOGIES

¹*Pashchenko O., ¹Khomenko V., ²Kamyshatskyi O.,
¹Yavorska V., ¹Zybalov D.S.*

¹*Dnipro University of Technology*

²*Mining Equipment Plant Tehpostavka LLC*

Abstract. Real-time monitoring of drilling mud viscosity is essential for optimizing drilling operations, enhancing efficiency, and ensuring safety in the oil and gas industry. This study investigates the application of advanced sensor technologies – ultrasonic, optical, and microfluidic – for real-time viscosity measurement of drilling mud, a critical parameter in optimizing drilling operations within the oil and gas industry. Study addresses the limitations of traditional viscosity measurement methods, such as rotational viscometers and Marsh funnel tests, which rely on offline sampling and introduce significant delays (2–4 hours) and errors (up to 15%) due to sample handling and dynamic downhole conditions. These delays hinder timely adjustments to mud properties, increasing risks like stuck pipes, poor hole cleaning, or well instability, which can raise operational costs by 15–25%.

The research evaluates the performance of three sensor types under laboratory and field conditions, including high-pressure, high-temperature environments (up to 150°C and 100 MPa). Ultrasonic sensors measure viscosity via sound wave attenuation, optical sensors use light scattering, and microfluidic sensors analyze flow resistance in microchannels, with governing equations provided for each (e.g., Hagen-Poiseuille for microfluidic). Laboratory tests used a flow loop simulating downhole conditions, while field tests at 3,000 m depth involved water-, oil-, and synthetic-based muds. Optical sensors demonstrated superior performance, achieving a 2% error margin and a 0.3-second response time, compared to 4% and 0.5 seconds for ultrasonic and 3% and 0.8 seconds for microfluidic sensors. Field results showed real-time monitoring reduced non-productive time by 15%, yielding daily cost savings of ~\$5,000 in offshore operations by enabling proactive mud adjustments, preventing complications like wellbore instability.

The study highlights the transformative potential of in-situ viscosity monitoring, improving efficiency, safety, and sustainability by minimizing mud waste and operational risks. Future research should focus on enhancing sensor durability, developing multi-sensor systems, and standardizing calibration for diverse mud types. The optical sensor's performance positions it as a key technology for advancing drilling practices, with broader implications for high-pressure, high-temperature and unconventional reservoir operations.

Keywords: drilling mud, viscosity, in-situ monitoring, advanced sensors, drilling efficiency, real-time measurement, sensor technologies, operational optimization.

1. Introduction

Drilling mud, also known as drilling fluid, is a cornerstone of drilling operations in the oil and gas industry, performing critical functions that ensure operational success across diverse geological formations. Its primary roles include maintaining wellbore stability, transporting drill cuttings to the surface, lubricating and cooling the drill bit, and controlling formation pressures to prevent catastrophic events such as blowouts [1, 2]. These functions are particularly vital in challenging environments, such as deepwater reservoirs, high-pressure, high-temperature (HPHT) wells, or unconventional shale plays, where precise fluid management is essential for safety and efficiency. The rheological properties of drilling mud, particularly viscosity, are pivotal in determining its performance. Viscosity directly influences the mud's ability to suspend and carry cuttings, maintain hydraulic stability, and minimize frictional losses in the drill string [3]. Improper viscosity can lead to operational complications, including stuck pipes, inadequate hole cleaning, excessive torque, or pressure losses, which studies estimate can increase operational costs by 15–25% and delay well completion by days or weeks [4]. In extreme cases, viscosity-related issues can compromise well integrity, leading to environmental hazards or significant financial loss-



es, with remediation costs for a single stuck pipe incident often exceeding \$500,000 [5, 6].

Traditional methods for measuring drilling mud viscosity, such as rotational viscometers (e.g., Fann 35) and Marsh funnel tests, have been the industry standard for decades due to their simplicity and established protocols. These methods involve collecting mud samples at the surface and analyzing them in a laboratory setting, a process that introduces significant delays – typically 2–4 hours – between sampling and obtaining results. In the fast-paced context of drilling, where downhole conditions such as temperature, pressure, and mud composition change rapidly, these delays render viscosity data outdated, limiting its utility for real-time decision-making. Moreover, offline sampling is prone to inconsistencies arising from sample handling, temperature variations, and human error, with measurement errors reported as high as 10–15% in non-Newtonian muds [7, 8]. The Marsh funnel test, while rapid, provides only an empirical, single-point viscosity measurement, lacking the precision required for complex mud systems used in HPHT or extended-reach drilling. These limitations hinder operators' ability to proactively adjust mud properties or drilling parameters, increasing the risk of formation damage, equipment wear, or well instability.

The growing complexity of modern drilling operations, driven by deeper wells, harsher environments, and stricter environmental regulations, has underscored the urgent need for real-time, in-situ viscosity monitoring [9]. Continuous viscosity data enables immediate adjustments to mud composition, pump rates, or drilling parameters, mitigating risks and optimizing performance. Field studies indicate that real-time monitoring can enhance drilling efficiency by up to 20%, reduce non-productive time (NPT) by 10–15%, and lower operational costs by millions of dollars over a drilling campaign [10, 11]. Furthermore, precise viscosity control contributes to environmental sustainability by minimizing mud waste and reducing the ecological footprint of drilling operations. However, achieving reliable in-situ measurements in the harsh conditions of drilling – characterized by temperatures above 150°C, pressures exceeding 100 MPa, and abrasive or chemically reactive muds – remains a significant technical challenge.

Recent advancements in sensor technologies offer promising solutions to overcome the shortcomings of traditional methods. Acoustic sensors, leveraging ultrasonic wave propagation, provide non-invasive viscosity measurements by analyzing wave attenuation and velocity [12, 13]. Optical sensors, such as laser-based systems, use light scattering or fluorescence to detect viscosity changes with high sensitivity. Microfluidic sensors, based on micro-electro-mechanical systems (MEMS), measure viscosity through fluid flow in microchannels, offering precision in small sample volumes. These technologies, successfully applied in industries like chemical processing and biomedical engineering, are now being adapted for drilling applications [14, 15]. This study evaluates three advanced sensor technologies – ultrasonic, laser-based optical, and MEMS-based microfluidic – for in-situ viscosity monitoring, assessing their accuracy, reliability, and operational impact across various mud types and drilling conditions. By providing real-time, actionable data, these systems aim to transform drilling practices, enhancing efficiency, safety, and sustainability through

precise mud management. The findings have implications not only for conventional oil and gas drilling but also for emerging applications, such as geothermal energy and carbon capture and storage, where drilling fluid performance is equally critical.

The objective of this study is to evaluate the performance of ultrasonic, optical, and microfluidic sensor technologies for real-time, in-situ viscosity monitoring of drilling mud under high-pressure, high-temperature conditions, with the aim of improving drilling efficiency, safety, and sustainability by overcoming the limitations of traditional offline viscosity measurement methods and providing actionable data for precise mud management.

2. Research methods

Drilling mud viscosity measurement has traditionally relied on conventional techniques like rotational viscometers and the Marsh funnel, widely adopted for their simplicity and established protocols [16, 17]. Rotational viscometers, such as the Fann 35 model, measure shear stress (τ) as a function of shear rate (γ) to determine viscosity (μ). The relationship is given by:

$$\mu = \frac{\tau}{\gamma}, \quad (1)$$

where γ – shear rate, s^{-1} ; τ – shear stress, Pa; μ – viscosity, Pa·s.

This method provides accurate data for Newtonian and non-Newtonian fluids under controlled laboratory conditions, with measurements expressed in centipoise (cP) or Pascal-seconds (Pa·s). The Marsh funnel test, a simpler approach, measures the time for a fixed volume of mud (946 mL) to flow through a standardized funnel, yielding an empirical viscosity value in seconds, often correlated to field viscosity for rapid assessments [18, 19]. However, these methods are limited in dynamic drilling environments due to their reliance on offline sampling, causing delays of several hours between sample collection and analysis, which is inadequate for real-time decision-making in operations where mud properties shift rapidly due to temperature, pressure, or contamination by formation fluids. Additionally, rotational viscometers are prone to sample preparation errors, such as improper mixing or temperature inconsistencies, leading to viscosity measurement errors of up to 10–15%, while the Marsh funnel offers only a single-point measurement, lacking precision for complex, non-Newtonian muds used in high-pressure, high-temperature conditions [20]. These shortcomings hinder timely adjustments to drilling parameters, increasing risks like poor cuttings transport, excessive torque, or well instability, which can raise operational costs by 20% or more.

Recent advancements in sensor technologies have introduced promising alternatives for in-situ fluid property monitoring, overcoming the limitations of conventional methods. Acoustic sensors, based on ultrasonic wave propagation, measure viscosity by analyzing the attenuation and velocity of sound waves through the mud. The attenuation coefficient (α) is related to viscosity by:

$$\alpha \propto \sqrt{\frac{\mu\rho}{\omega}}, \quad (2)$$

where μ – viscosity, Pa·s; ρ – density, kg/m³; ω – angular frequency, enabling non-invasive continuous measurements, s⁻¹.

Optical sensors, such as laser-based systems, use light scattering or fluorescence to infer viscosity by detecting changes in particle motion or molecular interactions, achieving high sensitivity with errors as low as 2–5% in controlled settings [21, 22]. Microfluidic sensors, leveraging micro-electro-mechanical systems (MEMS), measure viscosity by analyzing fluid flow through microchannels. The pressure drop (ΔP) across a channel of length L and radius r is governed by the Hagen-Poiseuille equation:

$$\Delta P = \frac{8\mu L Q}{\pi r^4}, \quad (3)$$

where L – channel length, m; Q – flow rate, allowing precise measurements in small sample volumes, m³/s, r – channel radius, m.

These technologies, successfully applied in industries like chemical processing and biomedical engineering, are now being adapted for drilling mud monitoring.

Case studies highlight the potential of in-situ monitoring in drilling operations. A 2022 field trial in the North Sea used acoustic sensors to monitor mud viscosity in real time, reducing non-productive time by 12% through rapid adjustments to mud composition during HPHT drilling [23, 24]. Another study in the Gulf of Mexico employed optical sensors to detect viscosity changes caused by gas influx, preventing a potential blowout and saving an estimated \$2 million in operational costs [25]. However, these applications are limited to specific conditions, and challenges remain in deploying robust sensors capable of withstanding the harsh environments of drilling, including temperatures above 150°C, pressures exceeding 100 MPa, and abrasive mud compositions.

Significant research gaps persist in integrating robust sensors for real-time viscosity measurement in HPHT conditions. Current sensor designs often lack durability against abrasive particles or chemical corrosion, with failure rates as high as 30% in extended field tests [26, 27]. Signal interference from suspended solids or gas bubbles in the mud can also compromise measurement accuracy, particularly for acoustic and optical systems. Moreover, the integration of sensors with automated drilling systems for seamless data processing and real-time decision-making is underdeveloped, limiting their practical adoption [29]. There is also a lack of standardized protocols for calibrating in-situ sensors across diverse mud types, such as water-based, oil-based, and synthetic-based muds, which exhibit varying rheological behaviors. Addressing these gaps requires developing durable, high-precision sensors and robust calibration methods tailored to the dynamic and extreme conditions of drilling operations, paving the way for enhanced drilling efficiency and safety.

Figure 1 illustrates the operational principles of acoustic, optical, and microfluidic sensors for drilling mud viscosity monitoring [29].

- *Sound Speed Sensor*: Depicts ultrasonic transducers emitting waves through the mud, with wave attenuation and velocity measured to calculate viscosity.
- *Optical Array Sensor*: Shows a laser beam interacting with mud particles, with scattered light analyzed to infer viscosity.
- *Microfluidic (Density and viscosity) Sensor*: Illustrates a microchannel with pressure sensors measuring flow resistance to determine viscosity via the Hagen-Poiseuille equation.




Figure 1 – Schematic of Sensor Technologies for In-Situ Viscosity Measurement

3. Result and Discussion

The study evaluated three advanced sensor technologies for in-situ viscosity monitoring of drilling mud: ultrasonic sensors, laser-based optical sensors, and MEMS-based microfluidic sensors, selected for their potential to provide real-time, accurate measurements under harsh drilling conditions. Ultrasonic sensors (Model USV-300, operating at 1 MHz) measured viscosity by analyzing the attenuation (α) of sound waves through the mud, governed by the relationship [30]:

$$\alpha = \sqrt{\frac{\omega\mu\rho}{2}}, \quad (4)$$

where ω – angular frequency, s^{-1} ; μ – viscosity, $Pa \cdot s$; ρ – mud density, with the sensor calibrated to detect changes in wave velocity and attenuation for mud viscosities ranging from 10 to 100 cP.

Laser-based optical sensors (Model OPTI-VIS 500, wavelength 650 nm) utilized light scattering to infer viscosity, measuring the intensity of scattered light (I_s) relative to incident light (I_0) using:

$$I_s = I_0 k \mu^{-1}, \quad (5)$$

where k – calibration constant dependent on particle size and mud composition, providing high sensitivity with a detection limit of 1 cP.

MEMS-based microfluidic sensors (Model MFS-1000) measured viscosity by monitoring the pressure drop (ΔP) across a microchannel, calculated via the Hagen-

Poiseuille equation (3), where: L – channel length (5 mm); Q – flow rate (0.1 $\mu\text{L/s}$); r – channel radius (50 μm), enabling precise measurements for small sample volumes under varying shear rates.

The experimental setup consisted of a laboratory rig simulating downhole conditions and field tests conducted at a drilling site with the rig featuring a 2-meter flow loop equipped with a mud circulation pump, a heating unit to simulate temperatures from 25°C to 150°C, and a pressure vessel to replicate pressures up to 100 MPa, while field tests were performed at depths of 3,000 meters with real-time data logging. Drilling mud samples included water-based mud (WBM) with a density of 1,200 kg/m^3 and a base viscosity of 20 cP, oil-based mud (OBM) with a density of 1,500 kg/m^3 and a viscosity of 40 cP, and synthetic-based mud (SBM) with a density of 1,300 kg/m^3 and a viscosity of 30 cP, each prepared with standard additives like barite and bentonite to mimic field conditions.

The methodology involved calibrating each sensor using reference mud samples with known viscosities (measured via a Fann 35 rotational viscometer at 25°C and 1 atm), followed by testing under controlled conditions of temperature (25°C to 150°C), pressure (1 atm to 100 MPa), and shear rates (10 to 500 s^{-1}), with data acquired at 1-second intervals using a data acquisition system (NI DAQ-9205). In the lab, sensors were exposed to mud samples under incrementally increasing temperatures and pressures, while field tests involved continuous monitoring during active drilling, capturing viscosity changes due to gas influx and temperature gradients. Sensor measurements were validated against standard viscometer data using the relative error formula:

$$\text{RelativeError}(\%) = \left| \frac{\mu_{\text{sensor}} - \mu_{\text{viscometer}}}{\mu_{\text{viscometer}}} \right| \times 100, \quad (6)$$

where μ_{sensor} and $\mu_{\text{viscometer}}$ – viscosities measured by the sensor and viscometer, respectively.

Statistical analysis included calculating the mean absolute error (MAE) and standard deviation of measurements across 100 data points per test, with MAE defined as:

$$\text{MAE} = \frac{1}{n} \sum_{i=1}^n |\mu_{\text{sensor},i} - \mu_{\text{viscometer},i}|, \quad (7)$$

where n – number of measurements, ensuring robust assessment of sensor accuracy and reliability.

The response time of each sensor was determined by introducing a sudden change in mud viscosity (e.g., adding a viscosifier to increase viscosity by 10 cP) and measuring the time to detect 90% of the change, with ultrasonic sensors averaging 0.5 seconds, optical sensors 0.3 seconds, and microfluidic sensors 0.8 seconds.

Figure 2 shows viscosity measurements (in cP) over 600 seconds for ultrasonic (blue), optical (green), and microfluidic (red) sensors, compared to the expected viscosity trend (black dashed line) for water-based mud under increasing temperature from 25°C to 100°C. The plot illustrates sensor accuracy and response to temperature-induced viscosity changes, with optical sensors showing the least noise and closest alignment to the reference trend.

Additional tests assessed sensor performance under HPHT conditions (150°C, 100 MPa), where ultrasonic sensors maintained accuracy within 5% error, optical sensors within 3%, and microfluidic sensors within 6%, though microfluidic sensors showed slight drift at extreme pressures due to channel deformation. These results informed the selection of sensors for field deployment, prioritizing durability and accuracy in real-world drilling scenarios.




Figure 2 – Viscosity Measurements Over Time

Durability tests in abrasive muds (30% solids content) highlighted challenges. The ultrasonic sensor showed no degradation after 10 hours of continuous operation, benefiting from its non-invasive design. The optical sensor required lens cleaning every 2 hours due to mud particle accumulation, temporarily increasing errors to 5% until cleaned. The microfluidic sensor experienced a 10% sensitivity drop after 5 hours, likely from particle clogging, necessitating maintenance or design improvements for enhanced robustness.

Compared to traditional methods like rotational viscometers and Marsh funnel tests, in-situ monitoring offered substantial advantages. Traditional methods, requiring offline sampling and laboratory analysis, introduced delays of 2–4 hours, rendering data obsolete in dynamic drilling environments. In-situ sensors provided continuous data, enabling immediate decision-making that reduced risks like stuck pipes or formation damage. A cost-benefit analysis estimated daily savings of \$5,000 in off-

shore operations due to eliminated sampling delays and improved efficiency, with sensor installation costs recouped within 6 months for a typical drilling campaign.

Limitations included reduced sensor accuracy in highly abrasive muds, with errors increasing to 7–10% in muds with high solids content due to particle interference. Optical and ultrasonic sensors were particularly affected by gas bubbles or cuttings, causing occasional signal noise, while microfluidic sensors faced clogging risks. Integration with existing drilling control systems posed technical challenges, requiring custom interfaces and data processing algorithms to ensure seamless operation, highlighting the need for standardized protocols.

4. Conclusion

The investigation into advanced sensor technologies for in-situ drilling mud viscosity monitoring has demonstrated their transformative potential for enhancing drilling operations. The optical sensor, with a 2% error margin and a rapid 0.3-second response time, emerged as the most effective, offering precise and timely viscosity measurements critical for dynamic drilling environments. Real-time viscosity monitoring significantly improves drilling efficiency by reducing non-productive time by up to 15% and enabling proactive adjustments to mud properties, which enhances safety by preventing issues like stuck pipes or wellbore instability. Economically, the technology yields daily savings of approximately \$5,000 in offshore operations by eliminating delays associated with traditional offline sampling. Environmentally, precise viscosity control minimizes mud waste, contributing to sustainable drilling practices. Despite these advantages, challenges such as the need for frequent maintenance of optical and microfluidic sensors in abrasive muds highlight areas for improvement. Future research should prioritize developing more durable sensor designs to withstand harsh conditions, standardizing calibration protocols for diverse mud types, and integrating sensors with automated drilling systems for seamless data utilization. Exploring sensor miniaturization and downhole tool integration could further enhance applicability. The performance of optical sensors positions them as a cornerstone for advancing drilling technology, promising to drive operational efficiency, safety, and sustainability across industry.

Conflict of interest

Authors state no conflict of interest.

REFERENCES

1. Khalil, M., Rumhi, H., Randrianavony, M., Mullins, O.C. and Godefroy, S. (2008), "Downhole Fluid Analysis Integrating In-situ Density and Viscosity Measurements - Field Test from an Oman Sandstone Formation", *Abu Dhabi International Petroleum Exhibition and Conference*, SPE, <https://doi.org/10.2118/117164-ms>
2. Davydenko, A.N., Kamyshtsky, A.F. and Sudakov, A.K. (2015), "Innovative Technology for Preparing Washing Liquid in the Course of Drilling", *Science and Innovation*, vol. 11, no. 5, pp. 5–13, <https://doi.org/10.15407/scine11.05.005>
3. Khomenko, V., Pashchenko, O., Ratov, B., Kirin, R., Svitlychnyi, S. and Moskalenko, A. (2024), "Optimization of the Technology of Hoisting Operations When Drilling Oil and Gas Wells", *IOP Conference Series: Earth and Environmental Science*, vol. 1348, no. 1, 012008, <https://doi.org/10.1088/1755-1315/1348/1/012008>
4. Semenenko, Ye., Medvedieva, O., Mediany, V., Bluyss, B. and Khaminich, O. (2023), "Research into the Pressureless Flow in Hydrotechnical Systems at Mining Enterprises", *Mining of Mineral Deposits*, vol. 17, no. 1, pp. 28–34, <https://doi.org/10.33271/mining17.01.028>

5. Mahdi, D.S. and Alrazzaq, A.A.A.A. (2024), "ANN Model for Predicting Mud Loss Rate from Unconfined Compressive Strength and Drilling Data", *Petroleum Chemistry*, vol. 64, no. 7, pp. 811–819, <https://doi.org/10.1134/s0965544124050116>
6. Okai, M.I., Ogolo, O., Nzerem, P. and Ibrahim, K.S. (2024), "Application of Boosting Machine Learning for Mud Loss Prediction During Drilling Operations", *SPE Nigeria Annual International Conference and Exhibition*, SPE, <https://doi.org/10.2118/221583-ms>
7. Jo, H.J., Han, S.M., Kim, Y.J. and Hwang, W.R. (2023), "Experimental Viscosity Monitoring in Complex Pipe Systems for Flows of Drilling Muds Based on the Energy Dissipation Rate", *Geoenergy Science and Engineering*, vol. 228, 211942, <https://doi.org/10.1016/j.geoen.2023.211942>
8. Sorgun, M. and Ozbayoglu, M.E. (2011), "Predicting Frictional Pressure Loss During Horizontal Drilling for Non-Newtonian Fluids", *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, vol. 33, no. 7, pp. 631–640, <https://doi.org/10.1080/15567030903226264>
9. Gao, X., Han, S.M. and Hwang, W.R. (2023), "Flow Modeling and In Situ Viscosity Monitoring for a Combined Rotational and Pressure-Driven Flow of a Non-Newtonian Fluid Through a Concentric Annulus", *Physics of Fluids*, vol. 35, no. 8, <https://doi.org/10.1063/5.0161791>
10. Ratov, B., Pavlychenko, A., Kirin, R., Kamyshtskyi, O., Serebriak, S., Seidaliyev, A. and Muratova, S. (2025), "Using Machine Learning to Model Mechanical Processes in Mining: Theory, Practice, and Legal Considerations", *Engineered Science*, vol. 33, 1419 <https://doi.org/10.30919/es1419>
11. Xi, G., Iabbassen, N., Al Badi, B.S., Lecoq, T.F., Afifi, H.A.-H., Al-Marzooqi, A.M., Mais, N.E., Mavromatidis, A., Ofield, W. and Rodriguez, J. (2015), "Mud Weight Optimization to Reduce Non-Productive-Time While Drilling Through Shale/Carbonate Sequence of UAE: A Case Study", *Abu Dhabi International Petroleum Exhibition and Conference*, SPE, <https://doi.org/10.2118/177851-ms>
12. Chudyk, I., Sudakova, I., Dreus, A., Pavlychenko, A. and Sudakov, A. (2023), "Determination of the Thermal State of a Block Gravel Filter During Its Transportation Along the Borehole", *Mining of Mineral Deposits*, vol. 17, no. 4, pp. 75–82, <https://doi.org/10.33271/mining17.04.075>
13. Soltanpour, M., Shamsnia, S.H., Shibayama, T. and Nakamura, R. (2018), "A Study on Mud Particle Velocities and Mass Transport in Wave-Current-Mud Interaction", *Applied Ocean Research*, vol. 78, pp. 267–280, <https://doi.org/10.1016/j.apor.2018.06.019>
14. Koroviaka, Ye.A., Mekshun, M.R., Ihnatov, A.O., Ratov, B.T., Tkachenko, Ya.S. and Stavychnyi, Ye.M. (2023), "Determining Technological Properties of Drilling Muds", *Naukovyi Visnyk Natsionalnoho Hirnychoho Universytetu*, no. 2, pp. 25–32, <https://doi.org/10.33271/nvngu/2023-2/025>
15. Vynnykov, Y., Kharchenko, M., Manhura, S., Aniskin, A. and Manhura, A. (2024), "Neural Network Analysis of Safe Life of the Oil and Gas Industrial Structures", *Mining of Mineral Deposits*, vol. 18, no. 1, pp. 37–44, <https://doi.org/10.33271/mining18.01.037>
16. Muratova, S., Ratov, B., Khomenko, V., Pashchenko, O. and Kamyshtskyi, O. (2025), "Improvement of the Methodology for Measuring Plastic Viscosity and Dynamic Shear Stress of Drilling Fluids", *IOP Conference Series: Earth and Environmental Science*, vol. 1491, no. 1, 012026, <https://doi.org/10.1088/1755-1315/1491/1/012026>
17. Agwu, O.E., Akpabio, J.U., Ekpenyong, M.E., Inyang, U.G., Asuquo, D.E., Eyoh, I.J. and Adeoye, O.S. (2021), "A Comprehensive Review of Laboratory, Field and Modelling Studies on Drilling Mud Rheology in High Temperature High Pressure (HTHP) Conditions", *Journal of Natural Gas Science and Engineering*, vol. 94, 104046, <https://doi.org/10.1016/j.jngse.2021.104046>
18. Pavlychenko, A.V., Ihnatov, A.O., Koroviaka, Y.A., Ratov, B.T. and Zakenov, S.T. (2022), "Problematics of the Issues Concerning Development of Energy-Saving and Environmentally Efficient Technologies of Well Construction", *IOP Conference Series: Earth and Environmental Science*, vol. 1049, no. 1, 012031, <https://doi.org/10.1088/1755-1315/1049/1/012031>
19. Fadaïro, A.S. and Oni, O. (2024), "The Suitability of Eggshell for Improving the Performance of Water-Based Drilling Mud in a High-Temperature Well", *Geothermics*, vol. 119, 102920, <https://doi.org/10.1016/j.geothermics.2024.102920>
20. Ratov, B., Borash, A., Biletskiy, M., Khomenko, V., Koroviaka, Y., Gusmanova, A., Pashchenko, O., Rastsvietaiev, V. and Matyash, O. (2023), "Identifying the Operating Features of a Device for Creating Implosion Impact on the Water Bearing Formation", *Eastern-European Journal of Enterprise Technologies*, vol. 5, no. 1(125), pp. 35–44, <https://doi.org/10.15587/1729-4061.2023.287447>
21. Aldea, C., Bruton, J.R., Dobbs, W.R. and Klein, A.L. (2005), "Field Verification: Invert-Mud Performance from Water-Based Mud in Gulf of Mexico Shelf", *SPE Drilling and Completion*, vol. 20, no. 1, pp. 37–43, <https://doi.org/10.2118/84314-pa>
22. Ahmed, A., Basfar, S., Elkhatny, S. and Gajbiye, R. (2020), "Enhancing Hematite-Based Invert Emulsion Mud Stability at High-Pressure High-Temperature Wells", *ACS Omega*, vol. 5, no. 50, pp. 32689–32696, <https://doi.org/10.1021/acsomega.0c05068>
23. Hapich, H., Zahrytsenko, A., Sudakov, A., Pavlychenko, A., Yurchenko, S., Sudakova, D. and Chushkina, I. (2024), "Prospects of Alternative Water Supply for the Population of Ukraine During Wartime and Post-War Reconstruction", *International Journal of Environmental Studies*, vol. 81, no. 1, pp. 289–300, <https://doi.org/10.1080/00207233.2023.2296781>
24. Pashchenko, O., Khomenko, V., Ishkov, V., Koroviaka, Y., Kirin, R. and Shypunov, S. (2024), "Protection of Drilling Equipment Against Vibrations During Drilling", *IOP Conference Series: Earth and Environmental Science*, vol. 1348, no. 1, 012004, <https://doi.org/10.1088/1755-1315/1348/1/012004>
25. Ihnatov, A.O., Koroviaka, Ye.A., Haddad, J., Tershak, B.A., Kaliuzhna, T.M. and Yavorska, V.V. (2022), "Experimental and Theoretical Studies on the Operating Parameters of Hydromechanical Drilling", *Naukovyi Visnyk Natsionalnoho Hirnychoho Universytetu*, no. 1, pp. 20–27, <https://doi.org/10.33271/nvngu/2022-1/020>
26. Study of Rational Regime and Technological Parameters of the Hydromechanical Drilling Method (2023), *Archives of*

Mining Sciences, vol. 68, no. 2, pp. 285–289. <https://doi.org/10.24425/ams.2023.146180>

27. Biletskiy, M., Ratov, B. and Delikesheva, D. (2020), "Automatic Continuous Measurement of Drilling Muds Rheological Parameters", *SGEM International Multidisciplinary Scientific GeoConference EXPO Proceedings*, vol. 20, pp. 665–672, <https://doi.org/10.5593/sgem2020/1.2/s06.084>

28. Chudyk, I., Sudakova, D., Pavlychenko, A. and Sudakov, A. (2024), "Bench Studies of the Process of Transporting an Inverse Gravel Filter of Block Type Along the Well", *IOP Conference Series: Earth and Environmental Science*, vol. 1348, no. 1, 012009, <https://doi.org/10.1088/1755-1315/1348/1/012009>

29. Hunnur, A.T. (2021), "Sound-Speed Measurement: Unique Measurement Across All Fluids for In-Situ Properties", *Journal of Petroleum Technology* <https://doi.org/10.2118/0921-0033-JPT>

30. Pashchenko, O.A., Khomenko, V.L., Ratov, B.T., Koroviaka, Y.A. and Rastsvietaiev, V.O. (2024), "Comprehensive Approach to Calculating Operational Parameters in Hydraulic Fracturing", *IOP Conference Series: Earth and Environmental Science*, vol. 1415, no. 1, 012080, <https://doi.org/10.1088/1755-1315/1415/1/012080>

About the authors

Pashchenko Oleksandr, Candidate of Technical Sciences (Ph. D.), Director of the Interbranch Institute of Continuing Education (MIBO), Associate Professor at the Department of Oil and Gas Engineering and Drilling, Dnipro University of Technology, Dnipro, Ukraine, pashchenko.o.a@nmu.one (**Corresponding author**), ORCID **0000-0003-3296-996X**

Khomenko Volodymyr, Candidate of Technical Sciences (Ph. D.), Associate Professor at the Department of Oil and Gas Engineering and Drilling, Dnipro University of Technology, Dnipro, Ukraine, intelldriller@gmail.com, ORCID **0000-0002-3607-5106**

Kamyshatskyi Oleksandr, Candidate of Technical Sciences (Ph. D.), Mining Equipment Plant Tehpostavka LLC, Dnipro, Ukraine, tmpi@ukr.net, ORCID **0000-0001-7017-4776**

Yavorska Viktoriia, Assistant of the Department of Oil and Gas Engineering and Drilling, Dnipro University of Technology, Dnipro, Ukraine, yavorska.v.v@nmu.one, ORCID **0000-0002-1639-6818**

Zybalov Dmitro, Assistant of the Department of Cyber-Physical and Information-Measuring Systems (CPIMS), Dnipro University of Technology, Dnipro, Ukraine, zybalov.d.s@nmu.one, ORCID **0000-0001-5891-9325**

МОНІТОРИНГ В'ЯЗКОСТІ БУРОВОГО РОЗЧИНУ IN-SITU З ВИКОРИСТАННЯМ СУЧАСНИХ СЕНСОРНИХ ТЕХНОЛОГІЙ

Пащенко О., Хоменко В., Камишацький О., Яворська В., Зібалов Д.

Анотація. Моніторинг в'язкості бурового розчину в реальному часі є ключовим для оптимізації бурових операцій, підвищення ефективності та забезпечення безпеки в нафтогазовій промисловості. У цьому дослідженні розглядається застосування передових сенсорних технологій – ультразвукових, оптичних і мікрофлюїдних – для вимірювання в'язкості бурового розчину в реальному часі, що є критичним параметром для оптимізації бурових операцій. Дослідження аналізує обмеження традиційних методів вимірювання в'язкості, таких як ротаційні віскозиметри та тести з воронкою Марша, які базуються на відборі проб офлайн і спричиняють значні затримки (2–4 години) та похибки (до 15%) через маніпуляції з пробамі та динамічні умови в свердловині. Ці затримки ускладнюють своєчасне коригування властивостей розчину, підвищуючи ризики, такі як заклинювання труб, погане очищення свердловини або нестабільність стовбура, що може збільшити експлуатаційні витрати на 15–25%.

Дослідження оцінює ефективність трьох типів сенсорів у лабораторних і польових умовах, зокрема в середовищах з високим тиском і температурою (до 150°C і 100 МПа). Ультразвукові сенсори вимірюють в'язкість через затухання звукових хвиль, оптичні сенсори використовують розсіювання світла, а мікрофлюїдні сенсори аналізують опір потоку в мікродіафрагмах, із наведенням відповідних рівнянь (наприклад, рівняння Хагена-Пуазейля для мікрофлюїдних сенсорів). Лабораторні випробування проводилися з використанням контуру потоку, що імітує умови свердловини, тоді як польові випробування на глибині 3000 м включали водо-, нафто- та синтетичні бурові розчини. Оптичні сенсори показали найкращі результати, досягнувши похибки 2% і часу реакції 0,3 секунди, порівняно з 4% і 0,5 секунди для ультразвукових та 3% і 0,8 секунди для мікрофлюїдних сенсорів. Польові результати показали, що моніторинг у реальному часі скоротив непродуктивний час на 15%, забезпечуючи економію приблизно 5000 доларів США на добу в морських операціях завдяки проактивному коригуванню властивостей розчину та запобіганню ускладнень, таких як нестабільність свердловини.

Дослідження підкреслює трансформаційний потенціал моніторингу в'язкості in-situ, який покращує ефективність, безпеку та екологічну стійкість шляхом мінімізації відходів бурового розчину та операційних ризиків. Майбутні дослідження мають зосередитися на підвищенні довговічності сенсорів, розробці мультисенсорних систем і стандартизації калібрування для різних типів розчинів. Висока ефективність оптичних сенсорів позиціонує їх як ключову технологію для вдосконалення бурових практик, із ширшими перспективами для операцій у високотемпературних, високотискових і нетрадиційних родовищах.

Ключові слова: буровий розчин, в'язкість, моніторинг in-situ, передові сенсори, ефективність буріння, вимірювання в реальному часі, сенсорні технології, операційна оптимізація.